



# TECHNICAL DATA SHEET

## C2 C3 5W-30 LS

Fully synthetic low SAPS engine oil

Product code: N230

### Product Description:

C2 C3 5W-30 LS is a fully synthetic multigrade engine oil formulated from hydrocracked synthetic base stocks, an advanced detergent-dispersant additive package, and shear stable polymers.

The low SAPS (sulphated ash, phosphorus and sulphur) formulation of C2 C3 5W-30 LS ensures compatibility with exhaust after treatment systems, such as particulate filters and catalytic converters.

### Benefits:

- Cost-effective coverage for a wide range of vehicles
- Exhaust after treatment system compatible
- Promotes reduced fuel consumption
- Ensures maximum engine protection
- Excellent high and low temperature stability

### Applications:

C2 C3 5W-30 LS is recommended for use in a wide variety of passenger cars and vans with petrol and diesel engines, including those that require a low SAPS oil with the following performance requirements.

### Product Specification:

ACEA	C2, C3
API	SN/CF

### Typical Test Data:

Density @ 15°C	0.855
Kinematic Viscosity @ 100°C (cSt)	12.0
Kinematic Viscosity @ 40°C (cSt)	72.7
Viscosity Index	162
Flash Point, COC (°C)	230
TBN (mg KOH/g)	7.1

### Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.